
Fast assembly concealed hinge

- **Intermat thick door hinge, door thickness up to 32 mm**
- **Opening angle 95°, drilling pattern TH 52 x 5.5 mm**




- Quality classification under EN 15570, Level 2
- For door thickness 14 - 32 mm
- Cup depth 10.5 mm
- Integrated adjustment of door offset +2.5 mm / -1.5 mm
- Integrated overlay adjustment +2 mm / -2 mm
- Height adjustment at mounting plate
- Steel nickel plated


Drilling pattern



full overlay
(Base B 12.5 mm)



half overlay
(Base B 3 mm)



inset
(Base B -3.5 mm)



With self closing feature (Intermat 9936)

Cup assembly	Mounting hole ø x T mm	full overlay		half overlay		inset	
		50 ea.	200 ea.	50 ea.	200 ea.	50 ea.	200 ea.
For screwing on	-	**0 073 913**	**1 058 365**	**0 073 917**	**1 058 366**	**0 073 921**	**1 058 367**
For pressing in	ø 10 x 11	**0 073 914**	**1 058 371**	**0 073 918**	**1 058 372**	**0 073 922**	**1 058 373**
with expanding sockets	ø 10 x 11	**9 043 586**	**9 043 629**	**9 043 587**	**9 043 630**	**9 043 588**	**9 043 631**

Without Silent System, for handleless applications (Intermat 9966)

Cup assembly	Mounting hole ø x T mm	full overlay		half overlay		inset	
		50 ea.	200 ea.	50 ea.	200 ea.	50 ea.	200 ea.
For screwing on	-	**9 044 858**	**9 044 850**	**9 044 868**	**9 044 860**	**9 044 878**	**9 044 870**
For pressing in	ø 10 x 11	**9 043 564**	**9 042 574**	**9 043 565**	**9 044 861**	**9 043 566**	**9 044 871**
with expanding sockets	ø 10 x 11	**9 043 567**	**9 044 857**	**9 043 568**	**9 044 867**	**9 043 569**	**9 044 877**